



## AquaPro MATTING AGENT 110 series

“AquaPro Matting Agent” is specially formulated for lowering the gloss level of water based paint. Desired gloss level of paint can be easily achieved.

Usage	Suitable for all AquaPro product series for lowering the gloss level of water based paint.
Finish	Matt
Color	Clear
Packing	500ml
Advantages	<ul style="list-style-type: none"> <li>✓ Smooth</li> <li>✓ User friendly</li> </ul>
Specific gravity	Approx. 1.27
Shelf Life	12 months
Application Method	<p><i>Note: Due to the nature of raw material, sedimentation and phase separation may occur during storage. This is a normal phenomenon. A thorough stir before use is necessary.</i></p> <p>Stir the water based matting agent thoroughly before use. Add the matting agent gradually into the water based paint and under stirring. Stir the paint mixture well before thinning.</p>
Thinning Ratio	
<ul style="list-style-type: none"> <li>- One component water based paint (e.g. AquaPro Enamel Paint, AquaPro Brushing Lacquer, etc.)</li> </ul>	Mix part A & part B of the two components water based paint well according to the coating instruction. Stir the water based matting agent thoroughly before use. Add the matting agent gradually into the paint mixed and under stirring. Stir the paint mixture well before thinning.
<ul style="list-style-type: none"> <li>- Two components water based paint (e.g. AquaPro Epoxy Paint, etc.)</li> </ul>	
<ul style="list-style-type: none"> <li>- Semi Gloss</li> </ul>	Add 1 part of matting agent into 10 parts of paint, actual effect depends on type of paint
<ul style="list-style-type: none"> <li>- Matt</li> </ul>	Add 2 parts of matting agent into 10 parts of paint, actual effect depends on type of paint

Technical Bulletin No.: 110/190618



Conditions	Stir the matting agent thoroughly before use. Store at cool, dry place. Avoid direct sunlight and > 30°C
Health & Safety Precautions	
– Ingestion	Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting.
– Eye contact	Flush immediately with water and get medical care.
– Skin contact	Flush immediately with water and remove contaminated clothing. If irritation persists, refer for medical attention.
– Inhalation	Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.

## NOTES

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.

Technical Bulletin No.: 110/190618

葉氏駱駝(香港)有限公司 YIP'S CAMEL (HONG KONG) LIMITED

香港灣仔告士打道77-79號富通大廈27樓

27/F., Fortis Tower, 77-79 Gloucester Road, Wanchai, Hong Kong

電話 Tel: (852) 2675 2333

傳真 Fax: (852) 2675 2332

電郵 Email: info@camel.com.hk

網址 Website: <http://www.camel.com.hk>

