

CAMEL

A066AF Anti-Fungus Solution

PRODUCT INTRODUCTION

Recommended	Suitable for interior & exterior concrete, plaster & brickwork.
Uses	
Description	This product is a water based microbiocide with persistent effectiveness. It is suitable
	for the disinfection of production facilities and wall surfaces.
Features	✓ Broad spectrum activity against fungi, bacteria & algae
	✓ The algae being not only killed but also lose their colour
	✓ Easy to apply
	✓ Low odour
	✓ Persistent effectiveness
Standard Packing	20L

TECHNICAL DATA

Base Resin	Quaternary ammonium compound
Color	Colourless liquid
Specific Gravity	Approx. 1 (at 25°C)

APPLICATION

Recommended	Water
Thinner	
Cleaning Solvent	Water

Remarks:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.



27/F, Fortis Tower, 77-79 Gloucester Road, Wan Chai, Hong Kong



CAMEL

AX483 High-build Epoxy Primer

APPLICATION

	ALLECATION
Method of Application	• Surfaces to be coated must be free from oil, grease, all chalked and scaled materials
	must be removed before application.
	For Exterior
	• Dilute 1 part of anti-fungus solution A066AF with 1 part of water by volume (In case the
	fungi are serious, less water may be added).
	Apply the thinned anti-fungus solution on infested surface.
	• Wait for about 5 - 15 mins (Wait for longer time if fungi are serious).
	Mechanical cleaning by high pressure water jet or scrub brush.
	For Interior
	• Dilute 1 part of anti-fungus solution A066AF with 0.5 part of water by volume (In case the
	fungi are serious, less water may be added).
	Apply the thinned anti-fungus solution on infested surface.
	• Wait for about 5 to 15 mins (Wait for longer time if fungi are serious).

STORAGE

Danasana Caada	Nian dan sanana sa da
Dangerous Goods	Non-dangerous goods
Classification	
Shelf-Life	24 Months
Application Conditions	• Maintain temperature in areas to receive coatings at minimum 7°C, during application
	and until anti-fungus solution has dried.
	• Adequate ventilated areas where anti-fungus solution is being applied. Maintain a
	reasonably dust-free atmosphere for duration of works.
	Protect adjacent surfaces not scheduled to receive coatings from damage and overcoat.
	Post "Wet Coating" signs while work is in progress and while coatings are curing.
Product Storage, Delivery & Handling	• Material to be delivered and stored in undamaged, original manufacturers' containers.
	Keep container closed when not in use.
	Shake well before use.
	Store at cool, dry place. Store above freezing point.
Health & Safety Precautions	• Ingestion: Send the affected person to hospital or obtain medical attention immediately.
	Do not induce vomiting.
	Eye contact: Flush immediately with water and get medical care.
	• Skin contact: Flush immediately with water and remove contaminated clothing. If
	irritation persists, refer for medical attention.
	• Inhalation: Remove the affected person to fresh air and obtain medical attention if rapid
	recovery does not occur.

Remarks:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.

