

VIVA RETARDER K809

D	wa	A.		In	two	4	ction	
r	ra	"	14.1		ıra		CHIAN	

RECOMMENDED USES	:	For removing of old emulsion paint film and also serve as an antiblush retarder.
DESCRIPTION	:	A quality thinner specially formulated for removing the old wall paint of latex products. It also exhibits very good blush resistance during the application of lacquers in high humidity.
STANDARD PACKING	:	1 ltr and 4 ltrs

Technical Data

BASE RESIN	:	Oxygenated Solvents
COLOR	:	Colourless liquid
DENSITY	:	Approx.0.88 kg/ltr
FLASH POINT	:	> 73 ⁰ F

Application

T F T T T T		
METHOD OF APPLICATION	:	For removal of the old emulsion paint film, dilute 1-2 parts of the
		retarder by 10 parts of water. Apply a generous amount of the
		mixture onto the surface. Allow time for the mixture to penetrate and
		strip off the softened film with a scraper.
	:	For anti-blush purpose, quantity to be added varies according to
		the weather and application conditions.

Safety Precaution

Daiety 1 recaution		
DANGEROUS GOODS CLASSIFICATION	:	Cat.5, Class 1, Division 1.
SHELF-LIFE	:	12 months.
HEALTH & SAFETY PRECAUTIONS	:	Ingestion : Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting.
		Skin contact: Flush immediately with water and remove contaminated clothing. Use soap if available. If irritation persists refer for medical attention.
		Eye contact : Flush immediately with water and get medical care.
		Inhalation : Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.