

CAMEL

ALGAE RESISTANCE PAINT

AX1000 SERIES

Product Introduction

RECOMMENDED USES	Suitable for interior and exterior surfaces of masonry, concrete and plaster..
DESCRIPTION	AX1000 series is a premium quality paint specially designed for protection and decoration of interior and exterior wall surface. ● Outstanding Opacity ● Excellent algae and fungus resistant ● Excellent Weather Resistance ● Compatible for Texture Coating ● Ease of maintenance ● Excellent dirt pick-up resistance
STANDARD PACKING	18L

Technical Data

BASE RESIN	Modified acrylic copolymer
COLOR	Tailor-made colors on requests
GLOSS	Semi-Gloss
CALCULATED COVERAGE	Approx. 15 sq. m/ ltr. at 25 microns dry film thickness depends on surface condition and application method.
DRYING TIME	Touch dry Hard dry
	30 minutes 1 hours

Application

RECOMMENDED THINNER	Water
CLEANING SOLVENT	Water

Notes: Product data is based on in-house testing methods modified from BS3900/ASTM.
Content will be updated without prior notice.
Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.

CAMEL

ALGAE RESISTANCE PAINT

AX1000 SERIES

Application

METHOD OF APPLICATION By Brush/Roller By Airless Spray By Conventional Spray	Ready for use, thinned if necessary. Dilute 10 parts of paint with 0-1 parts of water by volume. Dilute 10 parts of paint with 0-1 parts of water by volume. Dilute 10 parts of paint with 1-2 parts of water by volume. ● Thinning ratio can be adjusted according to actual application condition. ● Stir the paint well before use. ● Surfaces to be coated must be sound, clean, non-dusting, free from oil, grease, moisture and foreign particles. ● For recoating old surfaces, all chalked and scaled materials must be removed before painting. ● Painting is recommended to be carried out on fine day.
--	--

Safety Precaution

DANGEROUS GOODS CLASSIFICATION	Non-dangerous goods
SHELF-LIFE	36 Months
APPLICATION CONDITIONS	Maintain temperature in areas to receive coatings at minimum 7 deg. C, during application and until coatings have cured. Adequate ventilated areas where coating is being applied. Maintain a reasonably dust-free atmosphere for duration of works. Protect adjacent surfaces not scheduled to receive coating from damage and overcoat. Post 'Wet Coating' signs while work is in progress and while coating are curing.
HEALTH & SAFETY PRECAUTIONS	Ingestion : Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting. Skin contact : Flush immediately with water and remove contaminated clothing. Use soap if available. If irritation persists refer for medical attention. Eye contact : Flush immediately with water and get medical care. Inhalation : Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.
Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong	Non-Flat Coatings P09-06
VOC CONTENT (ready to use)	Not exceeding 150 gm/litre

Notes: Product data is based on in-house testing methods modified from BS3900/ASTM.
Content will be updated without prior notice.
Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.