

Camel

Professional Interior Emulsion

3 Years Anti-Mould

CC Series

PRODUCT INTRODUCTION

Recommended Uses	Suitable for interior ceilings and plastered cementitious walls.
Description	CC-Line is a high quality durable paint for the protection of interior wall surfaces. It is easy to apply paint with excellent hiding power and film build. It dries quickly to form a hardwearing, mould inhibitive film with long-lasting appearance. It is highly recommended by professional decorators.
Features	<ul style="list-style-type: none"> ● 3 years mould warranty ● Superior hiding ● Low VOC ● Good washability
3 Years Mould Warranty	<ul style="list-style-type: none"> ● Must wash mould area with AquaPro Super Anti-Mould Wash 111 with clean towel ● Apply 2 coats of Camel Professional Interior Emulsion – 3 Years Anti-Mould according to instruction ● Humidity should not exceed 85% upon application ● Please retain purchase receipt, batch number and application date. ● Contact our Technical Services Team on 3473 3300 for assistance if mould occur ● We will compensate to the same value of paint product in the unlikely event of mould resistance failure
Standard Packing	1 liter, 4 liters & 18 liters.

TECHNICAL DATA

Base Resin	Acrylic / Acetate copolymer
Color	Standard colors or personalized color by computerized tinting machine
Finish	Matt
Calculated Coverage	Around 20m ² /ltr. @ 25 microns dry film thickness per coat Actual coverage depends on surface conditions and also application conditions.
Drying Time (@ 25°C)	<ul style="list-style-type: none"> ● Touch Dry --- 1 hour ● Hard Dry --- 2 hours ● Overcoating --- Minimum --- 2 hours

APPLICATION

Recommended Primer	Camel Alkali Resistant wall Sealer MA473 or Camel Professional Water Sealer S200
Recommended Thinner	Clear Water
Method of Application	<ul style="list-style-type: none"> ● Ready-to-use after thinning with clear water and stirring thoroughly ● Thinning Ratio <ul style="list-style-type: none"> Brush --- Dilute 10 parts of the paint with 3 parts of clear water (10 : 3 by volume). Roller --- Dilute 10 parts of the paint with 2 parts of clear water (10 : 2 by volume) Airless Spray --- Dilute 10 parts of the paint with 2 parts of clear water (10 : 2 by volume) Conventional Spray --- Dilute 10 parts of the paint with 4 parts of clear water (10 : 4 by volume) ● Recommended no. of coats : 2 coats

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.

Camel

Professional Interior Emulsion

3 Years Anti-Mould

CC Series

APPLICATION

Surface Preparation	<ul style="list-style-type: none"> ● For new wall --- The substrate should be cured at least 30 days. The alkalinity (pH) of the surface should be < 10 before painting and water content of the substrate should be < 15%. --- Fill up cracks and depression to get a smooth surface with appropriate filler. --- Ensure the surfaces to be coated are sound, clean, free from dust, rust, oil, grease, moisture and foreign matters. ● For recoated surface --- All chalked and scaled materials must be removed before painting. --- Apply patching paste to get a smooth surface before painting. --- Apply AquaPro Super Anti-Mould Wash 111 (dilute 2 parts of Super Anti-Mould Wash 111 with 1 part of clear water) on mould affected area, and stay more than 6 hours. --- After 6 hours, clean with new towel and water. --- Use new towels in each process, to avoid cross contamination. --- Let surface dry, then apply 2 coats of Camel Professional Interior Emulsion – 3 Years Anti Mould CC- series. --- Ensure the surfaces to be coated are sound, clean, free from dust, rust, oil, grease, moisture and foreign matters.
---------------------	--

SAFETY PRECAUTION

Dangerous Goods Classification	Not applicable.
Shelf-Life	36 Months.
Application Conditions	<ul style="list-style-type: none"> ● Maintain temperature in areas to receive coatings at minimum 5 deg. C, during application and until coatings have cured. ● Avoid applying the product when relative humidity above 85%. ● Adequately ventilate areas where coatings are being applied. Maintain a reasonably dust-free atmosphere for duration of work. ● Protect adjacent surfaces not scheduled to receive coatings from damage and overcoat. ● Post “Wet Coating” signs while work is in progress and while coatings are curing.
Product Storage, Delivery & Handling	<ul style="list-style-type: none"> --- Material to be delivered and stored in undamaged, original manufacturers’ containers. --- Keep container closed when not in use. --- Store at cool, dry place. Store above freezing point.
Health & Safety Precautions	<ul style="list-style-type: none"> ● Ingestion --- Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting. ● Eye contact --- Flush immediately with water and get medical care. ● Skin --- Flush immediately with water and remove contaminated clothing. If irritation persists, refer for medical attention. ● Inhalation --- Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.
Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong	Flat Coatings P09-02
VOC content (ready to use)	Not exceeding 50gm/litre

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.