

CAMEL ACRYLIC EMULSION MA400 SERIES

Product Introduction

RECOMMENDED USES	Suitable for cementitious and plastered interior wall
DESCRIPTION	MA400 line is a premium quality matt emulsion paint specially designed for protection and decoration of cementitious and plastered interior wall surfaces. ● Anti-carbonation ● Outstanding Opacity ● Fungus Resistance ● Ease of Application ● Excellent Washability ● Ease of maintenance
STANDARD PACKING	18L

Technical Data

BASE RESIN	Acrylic Copolymer
COLOR	Tailor-made colors on requests
GLOSS	Matt
CALCULATED COVERAGE	Approx. 12 sq. m/ ltr. at 30 microns dry film thickness depends on surface condition and application method.
DRYING TIME	Touch dry Hard dry ≤ 30 minutes ≤ 1 hour

Notes: Product data is based on in-house testing methods modified from BS3900/ASTM.

Content will be updated without prior notice.

Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.

CAMEL ACRYLIC EMULSION MA400 SERIES

Application

RECOMMENDED THINNER	Water
METHOD OF APPLICATION	:
Recommended coats	2 coats
By Brush/ Roller	Ready for use, thinned if necessary. Dilute 10 parts of paint with 0-1 parts of water by volume.
By Airless Spray	Dilute 10 parts of paint with 0-1 parts of water by volume.
By Conventional Spray	Dilute 10 parts of paint with 1-2 parts of water by volume.
	● Thinning ratio can be adjusted according to actual application condition. ● Stir the paint well before use. ● Surfaces to be coated must be sound, clean, non-dusting, free from oil, grease, moisture and foreign particles. ● For recoating old surfaces, all chalked and scaled materials must be removed before painting. ● Painting is recommended to be carried out on fine day.

Notes: Product data is based on in-house testing methods modified from BS3900/ASTM.

Content will be updated without prior notice.

Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.

CAMEL ACRYLIC EMULSION MA400 SERIES

Safety Precaution	
DANGEROUS GOODS CLASSIFICATION	Non-dangerous goods
SHELF-LIFE	36 Months
APPLICATION CONDITIONS	● Maintain temperature in areas to receive coatings at minimum 6 deg. C, during application and until coatings have cured. ● Adequately ventilate areas where coatings are being applied. Maintain a reasonably dust-free atmosphere for duration of work. ● Protect adjacent surfaces not scheduled to receive coatings from damage and overcoat. ● Post “Wet Coating” signs while work is in progress and while coatings are curing.
HEALTH & SAFETY PRECAUTIONS	Ingestion : Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting. Skin contact : Flush immediately with water and remove contaminated clothing. Use soap if available. If irritation persists refer for medical attention. Eye contact : Flush immediately with water and get medical care. Inhalation : Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.
Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong	Flat Coatings P09-02
VOC CONTENT (ready to use)	Not exceeding 50 gm/litre

Notes: Product data is based on in-house testing methods modified from BS3900/ASTM.

Content will be updated without prior notice.

Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.