

Camel

Professional Interior Emulsion

MA477 Series

PRODUCT INTRODUCTION

Recommended Uses	Suitable for interior surfaces of masonry, concrete and plaster.
Description	This quality vinyl acrylic copolymer emulsion paint MA477 is specially designed for interior decoration and protection of walls and ceilings.
Features	<ul style="list-style-type: none"> ● Best Value ● Extreme Matt ● Anti-Condensation
Standard Packing	18L

TECHNICAL DATA

Base Resin	Vinyl Acetate/Acrylic Copolymer Emulsion
Color	As per color card. Tailor-made colors on requests
Finish	Matt
Calculated Coverage	Around 12m ² /ltr. @25 microns dry film thickness per coat Actual coverage depends on surface conditions and also application conditions.
Drying Time	<ul style="list-style-type: none"> ● Touch Dry --- 1 hour ● Hard Dry --- 2 hours ● Over coating --- minimum 4 hours, maximum indefinite.

APPLICATION

Recommended Primer	Camel Alkali Resistant Wall Sealer MA473 or Camel Professional Water Sealer S200
Recommended Thinner	Clear water
Method of Application	<ul style="list-style-type: none"> ● Thinning Ratio <ul style="list-style-type: none"> By Brush --- Dilute 10 parts of paint with 3 parts of clear water by volume. By Roller --- Dilute 10 parts of paint with 2 parts of clear water by volume. By Airless Spray --- Dilute 10 parts of paint with 2 parts of clear water by volume. By Conventional Spray --- Dilute 10 parts of paint with 4 parts of clear water by volume. ● Recommended no. of coats --- 2 coats
Recommendations for Application	<ul style="list-style-type: none"> ● Painting is recommended to carry out on fine day. ● Surfaces to be coated must be sound, clean, free from dust, rust, oil, grease, moisture and foreign matters. For recoating old surfaces, all chalked and scaled materials must be removed before painting. ● Stir the paint well before use.

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.

Camel Professional Interior Emulsion MA477 Series

SAFETY PRECAUTION	
Dangerous Goods Classification	Not applicable.
Shelf-Life	36 Months.
Application Conditions	<ul style="list-style-type: none"> ● Maintain temperature in areas to receive coatings at minimum 6 deg. C, during application and until coatings have cured. ● Adequately ventilate areas where coatings are being applied. Maintain a reasonably dust-free atmosphere for duration of work. ● Protect adjacent surfaces not scheduled to receive coatings from damage and overcoat. ● Post “Wet Coating” signs while work is in progress and while coatings are curing.
Product Storage, Delivery & Handling	<ul style="list-style-type: none"> ● Net Weight --- Around 18kg (values may vary with colors) ● Material to be delivered and stored in undamaged, original manufacturers’ containers. ● Keep container closed when not in use. ● Store at cool, dry place.
Health & Safety Precautions	<ul style="list-style-type: none"> ● Ingestion --- Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting. ● Eye contact --- Flush immediately with water and get medical care. ● Skin contact --- Flush immediately with water and remove contaminated clothing. If irritation persists, refer for medical attention. ● Inhalation --- Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.
Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong	Flat Coatings P09-02
VOC content (ready to use)	Not exceeding 50gm/litre

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.