



CAMEL

S200 PROFESSIONAL WATER SEALER

PRODUCT INTRODUCTION

RECOMMENDED USES	Suitable for interior surfaces of masonry, concrete and plaster.
DESCRIPTION	This Sealer specially for priming well-prepared interior plastered cementitious wall surfaces. It is suitable for decoration and protection of interior walls. It forms a tough film of excellent hiding and excellent alkali resistance.
FEATURES	<ul style="list-style-type: none"> ✓ Excellent hiding ✓ Excellent binding strength ✓ Excellent adhesion on substrate ✓ Excellent alkali resistance ✓ Ease of application
STANDARD PACKING	1L & 4L

TECHNICAL DATA

BASE RESIN	Acrylic Copolymer
COLOR	White
FINISH	Matt
VISCOSITY	> 80 KU (25°C)
SPECIFIC GRAVITY	Approx. 1.25 ~ 1.35
FINENESS	< 60 μ m
VOLUME SOLIDS	Approx. 25 %
CALCULATED COVERAGE	Around 12.5 m ² /ltr. @20 microns dry film thickness per coat
Recommended Film Thickness	Brush/ Roller --- Wet : 60 - 80 microns --- Dry : 15 - 20 microns
Drying Time	Touch Dry - 1hour Hard Dry - 2hours Over coating@20°C - Minimum 4hours, Maximum 72hours

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.



CAMEL

S200 PROFESSIONAL WATER SEALER

APPLICATION

SURFACE PREPARATION	<ul style="list-style-type: none"> Fresh concrete must be allowed to cure sufficiently (approx. 28 days) prior to application. Remove loosely adhering concrete or mortar by chipper, then seal up any cracks or joints by filling with appropriate filler. Areas where previous coating is loose and peeling should be completely removed by hand cleaning with wire brushes, scrapers or chippers.
RECOMMENDED APPLICATION	<ul style="list-style-type: none"> Painting is recommended to carry out on fine day. Surfaces to be coated must be sound, clean, free from dust, rust, oil, grease, moisture and foreign matters. For recoating old surfaces, all chalked and scaled materials must be removed before painting. Stir the paint well before use.

SAFETY PRECAUTION

DANGEROUS GOODS CLASSIFICATION	Not applicable.
SHELF-LIFE	24 Months
APPLICATION CONDITIONS	<ul style="list-style-type: none"> Maintain temperature in areas to receive coatings at minimum 7 deg. C, maximum 85% relative humidity during application and until coatings have cured. Adequately ventilate areas where coatings are being applied. Maintain a reasonably dust-free atmosphere for duration of work. Protect adjacent surfaces not scheduled to receive coatings from damage and overcoat. Post "Wet Coating" signs while work is in progress and while coatings are curing.
PRODUCT STORAGE & HANDLING	<ul style="list-style-type: none"> Material to be delivered and stored in undamaged, original manufacturers' containers. Keep container closed when not in use. Stir the paint well before use. Store at cool, dry place.
HEALTH & SAFETY PRECAUTIONS	<ul style="list-style-type: none"> Ingestion: Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting. Eye contact: Flush immediately with water and get medical care. Skin contact: Flush immediately with water and remove contaminated clothing. If irritation persists, refer for medical attention. Inhalation: Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.
TYPE OF REGULATED PAINT	Primers, Sealers and Undercoaters P10-11 (under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong))
VOC CONTENT	Not exceeding 200gm/litre (ready to use)

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.