

CAMEL MULTI LAYER EXTERIOR PAINT 351 SERIES

Product Introduction

RECOMMENDED USES	:	Suitable for exterior surfaces of masonry, concrete and plaster.
DESCRIPTION	:	351 series is a premium quality emulsion paint specially designed for protection and decoration of exterior wall surface. ● Fulfill the quality requirement of multi-layer acrylic paint of Hong Kong Housing Authority HKHA General Specification 2013 Section 16.25 ● Good hiding ● Excellent algae and fungus resistant ● Excellent Weather Resistance ● Compatible for Texture Coating ● Excellent Washability ● Smooth surface, good anti-dirt pick up resistance
STANDARD PACKING	:	18 liters

Technical Data

BASE RESIN	:	Acrylic Polymer
COLOR	:	Tailor made colors on request.
FINISH	:	Semi Gloss
CALCULATED COVERAGE	:	Approx. 14 sq. m/ ltr. at 30 microns dry film thickness.
DRYING TIME		
Touch Dry	:	30 minutes
Hard Dry	:	1 hours
Over coating@25°C	:	Minimum 3 hours

Notes: Product data is based on in-house testing methods modified from JIS / BS3900/ASTM.
 Content will be updated without prior notice.
 Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.

CAMEL MULTI LAYER EXTERIOR PAINT 351 SERIES

Application

RECOMMENDED PRIMER	:	Camel Multi Layer Interior & Exterior Wall Sealer 363
RECOMMENDED UNDERCOAT	:	Camel Multi Layer Textured Undercoat 352
RECOMMENDED THINNER	:	Water
METHOD OF APPLICATION		
Recommended coats	:	2 coats
By Brush, Roller or Airless Spray	:	Ready for use, thinned if necessary.
	:	Painting is recommended to carry out on fine day.
	:	Surfaces to be coated must be sound, clean, non-dusting, free from oil, grease, moisture and foreign particles.
	:	For recoating old surfaces, all chalked and scaled materials must be removed before painting.
	:	

Notes: Product data is based on in-house testing methods modified from JIS / BS3900/ASTM.
Content will be updated without prior notice.
Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.

CAMEL MULTI LAYER EXTERIOR PAINT 351 SERIES

Safety Precaution

DANGEROUS GOODS CLASSIFICATION	:	Not applicable
SHELF-LIFE	:	36 months
APPLICATION CONDITIONS	:	Maintain temperature in areas to receive coatings at minimum 7 deg. C, during application and until coatings have cured. Adequately ventilate areas where coatings are being applied. Maintain a reasonably dust-free atmosphere for duration of work. Protect adjacent surfaces not scheduled to receive coatings from damage and overcoat. Post “Wet Coating” signs while work is in progress and while coatings are curing.
PRODUCT STORAGE & HANDLING	:	● Net Weight Around 24kg ● Delivery & Handling Material to be delivered and stored in undamaged, original manufacturers’ containers. Keep container closed when not in use. Stir the paint well before use. Store at cool, dry place.
HEALTH & SAFETY PRECAUTIONS	:	Ingestion : Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting. Skin contact : Flush immediately with water and remove contaminated clothing. Use soap if available. If irritation persists refer for medical attention. Eye contact : Flush immediately with water and get medical care. Inhalation : Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.
REGULATED PRODUCT CODE	:	Non-flat Coatings P09-06
VOC CONTENT	:	≤ 150g/ltr

Notes: Product data is based on in-house testing methods modified from JIS / BS3900/ASTM.
Content will be updated without prior notice.
Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.