

CAMEL MULTI LAYER TEXTURED UNDERCOAT 352

Product Introduction

RECOMMENDED USES	:	Suitable for interior and exterior surfaces of masonry, concrete and plaster.
DESCRIPTION	:	352 line is a high quality water-borne product for the protection and decoration of interior and exterior wall surface. ● Fulfill the quality requirement of multi-layer acrylic paint of Hong Kong Housing Authority HKHA General Specification 2013 Section 16.25 ● Excellent adhesion ● Excellent water resistance ● Excellent weather resistance ● Tough and durable ● Good spraying properties
STANDARD PACKING	:	24kg

Technical Data

BASE RESIN	:	Acrylic
COLOR	:	Greyish
FINISH	:	Matt
CALCULATED COVERAGE		
Fine Texture	:	Approx. 2.5 sq. m/kg
Medium Texture	:	Approx. 1.7 sq. m/kg
DRYING TIME	:	
Touch Dry	:	2 hours
Hard Dry	:	24 hours

Application

RECOMMENDED SEALER	:	Camel Multi Layer Interior & Exterior Wall Sealer 363
RECOMMENDED THINNER	:	Water
METHOD OF APPLICATION	:	By Spraying: Ready for use. Only small amount of water is added for thinning if necessary. Depending on the requirement, adjust spray pressure, nozzle size and spray distance to achieve effect desired. To obtain “head cut” pattern, after 5 minutes from spraying, different sizes of texture can be obtained by pressing with roller soaked with turpentine or kerosene.

Notes: Product data is based on in-house testing methods modified from JIS / BS3900/ASTM.

Content will be updated without prior notice.

Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.

Technical Bulletin No.352/230327

CAMEL MULTI LAYER TEXTURED UNDERCOAT 352
--

Safety Precaution

DANGEROUS GOODS CLASSIFICATION	:	Not applicable
SHELF-LIFE	:	24 months
APPLICATION CONDITIONS	:	Maintain temperature in areas to receive coatings at minimum 8 deg. C, during application and until coatings have cured. Adequately ventilate areas where coating are being applied. Maintain a reasonably dust-free atmosphere for duration of works. Protect adjacent surfaces not scheduled to receive coating from damage and overcoat. Post 'Wet Coating' signs while work is in progress and while coating are curing.
PRODUCT STORAGE & HANDLING	:	● Net Weight ● Delivery & Handling Around 24kg Material to be delivered and stored in undamaged, original manufacturers' containers. Keep container closed when not in use. Stir the paint well before use. Store at cool, dry place.
HEALTH & SAFETY PRECAUTIONS	:	Ingestion : Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting. Skin contact : Flush immediately with water and remove contaminated clothing. Use soap if available. If irritation persists refer for medical attention. Eye contact : Flush immediately with water and get medical care. Inhalation : Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.
REGULATED PRODUCT CODE	:	Granite Look-alike Coatings or Textured Undercoats P09-03
VOC CONTENT	:	≤ 100g/ltr

Notes: Product data is based on in-house testing methods modified from JIS / BS3900/ASTM.
Content will be updated without prior notice.
Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.