

Camel Multi Layer Interior & Exterior Wall Sealer 363
--

Product Introduction

RECOMMENDED USES	:	Suitable for interior and exterior surfaces of concrete, cement, plaster and masonry.
DESCRIPTION	:	This sealer is formulated specially for priming well-prepared interior plastered or exterior wall surfaces. It forms a tough film of excellent adhesion, hiding, binding and also resistance to alkali & water.
FEATURES		● Fulfill the quality requirement of multi-layer acrylic paint of Hong Kong Housing Authority HKHA General Specification 2013 Section 16.25 ● Excellent Adhesion to substrate ● Excellent Hiding ● Excellent Binding Strength ● Excellent Water and Alkali Resistance ● Low VOC & no odour ● Ease of Application
STANDARD PACKING	:	18L

Technical Data

BASE RESIN	:	Acrylic copolymer
COLOR	:	White
FINISH	:	Matt
CALCULATED COVERAGE		Around 15m ² /ltr. @25 microns dry film thickness per coat
DRYING TIME		
Touch Dry	:	1 hour
Hard Dry	:	2 hours

Notes: Product data is based on in-house testing methods modified from JIS / BS3900/ASTM.

Content will be updated without prior notice.

Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.

Technical Bulletin No.363/230327

Camel
Multi Layer Interior & Exterior Wall Sealer
363

Application

RECOMMENDED THINNER	:	Water
METHOD OF APPLICATION	:	Ready-to-use after thinning with clear water and stirring thoroughly
		Thinning Ratio
By Brush	:	Dilute 10 parts of the paint with 2.4 part of water (10 : 2.4 by volume).
By Roller	:	Ready for use, thin if necessary.
		● Recommended no. of coats --- 1 coat ● Recommended Application
		Painting is recommended to carry out on fine day.
		Surfaces to be coated must be sound, clean, free from dust, rust, oil, grease, moisture and foreign matters. For recoating old surfaces, all chalked and scaled materials must be removed before painting.
		Fresh concrete must be allowed to cure sufficiently (i.e. approximately 28 days) prior to application.

Notes: Product data is based on in-house testing methods modified from JIS / BS3900/ASTM.

Content will be updated without prior notice.

Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.

Technical Bulletin No.363/230327

Camel Multi Layer Interior & Exterior Wall Sealer 363
--

Safety Precaution

DANGEROUS GOODS CLASSIFICATION	:	Not applicable
SHELF-LIFE	:	24 months.
APPLICATION CONDITIONS	:	Maintain temperature in areas to receive coatings at minimum 7 deg. C, during application and until coatings have cured. Adequately ventilate areas where coating are being applied. Maintain a reasonably dust-free atmosphere for duration of works. Protect adjacent surfaces not scheduled to receive coating from damage and overcoat. Post 'Wet Coating' signs while work is in progress and while coatings are curing.
PRODUCT STORAGE & HANDLING	:	● Net Weight : Around 22kg ● Delivery & Handling : Material to be delivered and stored in undamaged, original manufacturers' containers. : Keep container closed when not in use. : Stir the paint well before use. : Store at cool, dry place.
HEALTH & SAFETY PRECAUTIONS	:	Ingestion : Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting. Skin contact : Flush immediately with water and remove contaminated clothing. Use soap if available. If irritation persists refer for medical attention. Eye contact : Flush immediately with water and get medical care. Inhalation : Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.
TYPE OF REGULATED PAINT UNDER THE AIR POLLUTION CONTROL (Volatile Organic Compounds) REGULATION OF HONG KONG	:	Primers, Sealers and Undercoaters P10-11
VOC CONTENT (ready to use)	:	Not exceeding 200gm/litre

Notes: Product data is based on in-house testing methods modified from JIS / BS3900/ASTM.

Content will be updated without prior notice.

Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.

Technical Bulletin No.363/230327