



AQUAPRO PVC PIPE PRIMER

453 SERIES

“AquaPro PVC Pipe Primer 453 Series” is formulated specially for protection and decoration of interior & exterior PVC Pipes.

Usage	Suitable for interior and exterior surface of Unplasticized PVC (U-PVC) pipes.
Finish	Matt
Color	White
Packing	4 Liter
Advantages	<ul style="list-style-type: none"> ✓ Strong Binding – Protective film with excellent binding strength ✓ Adhesion – Excellent adhesion to Unplasticized PVC surfaces ✓ Resistant to water & alkali – Good protection to surfaces ✓ Environmental friendly – Low VOC & no odour ✓ Ease of application
Base Resin	Acrylic copolymer
Drying Time	
– Touch Dry	1 hour
– Hard Dry	2 hours
– Overcoating	Minimum 3 hours, Maximum 72 hours
Coverage	Around 16m ² /ltr. @25 microns dry film thickness per coat Actual coverage depends on surface conditions and also application conditions.
Shelf Life	24 months
Application Method	Ready-to-use after thinning with clear water and stirring thoroughly.
Recommended No. of coat	1 coat
Thinning Ratio	
– Brush	Dilute 10 parts of the paint with 1 part of clear water (10%)
– Roller	Ready for use, thin if necessary
Application	<ol style="list-style-type: none"> 1. Surfaces to be coated must be sound, clean, free from dust, rust, oil, grease, moisture and foreign matters. For recoating old surfaces, all chalked and scaled materials must be removed before painting. 2. Stir the paint well before use. 3. If the mixture thickens or spoils, do not thin. Properly throw it away. Mix fresh materials again for new paint.

Technical Bulletin No.: 453/250626

Conditions	<ul style="list-style-type: none"> - Maintain temperature in areas to receive coatings at minimum 7°C during application and until coatings have cured. - Adequately ventilate areas where coatings are being applied. Maintain a reasonably dust-free atmosphere for duration of work. - Protect adjacent surfaces not scheduled to receive coatings from damage and overcoat. - Post "Wet Coating" signs while work is in progress and while coatings are curing. - Material to be delivered and stored in undamaged, original manufacturers' containers. - Keep container closed when not in use - Store at cool, dry place. Store above freezing point.
Health & Safety Precautions <ul style="list-style-type: none"> - <i>Ingestion</i> - <i>Eye contact</i> - <i>Skin contact</i> - <i>Inhalation</i> 	<p>Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting.</p> <p>Flush immediately with water and get medical care.</p> <p>Flush immediately with water and remove contaminated clothing. If irritation persists, refer for medical attention.</p> <p>Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.</p>

Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong: Primers, Sealers and Undercoaters P10-11

VOC content (ready to use): Not exceeding 200gm/Liter

NOTES

- Product data is based on in-house testing methods modified from BS3900/ ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.

Technical Bulletin No.: 453/230323