

## **CAMEL**

# **CX414 PROFESSIONAL RETARDER**

#### **PRODUCT INTRODUCTION**

RECOMMENDED USES	For removing of old emulsion paint film and also serve as an anti-blush retarder.
DESCRIPTION	A quality thinner specially formulated for removing the old wall paint of latex products. It also exhibits very good blush resistance during the application of lacquers in high humidity.
STANDARD PACKING	1 ltr and 4 ltrs

#### **TECHNICAL DATA**

BASE RESIN	Glycol ether
COLOR	Colourless liquid

### **APPLICATION**

METHOD OF APPLICATION	For removal of the old emulsion paint film, dilute 1-2 parts of the retarder by 10 parts of water. Apply a generous amount of the mixture onto the surface. Allow time for the mixture to penetrate and strip off the softened film with a scraper.
	For anti-blush purpose, quantity to be added varies according to the weather and application conditions.

#### **SAFETY PRECAUTION**

DANGEROUS GOODS	Class 3
CLASSIFICATION	
SHELF-LIFE	24 Months
HEALTH & SAFETY PRECAUTIONS	Ingestion: Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting.  Skin contact: Flush immediately with water and remove contaminated clothing. Use soap if available. If irritation persists refer for medical attention.  Eye contact: Flush immediately with water and get medical care.  Inhalation: Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.

#### Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.

