



## CAMEL PROFESSIONAL WHITE TURPENTINE CX316

### Product Introduction

RECOMMENDED USES	:	For enamel and varnish products.
DESCRIPTION	:	A standard turpentine is formulated with the good balance of the solvency and volatility.
STANDARD PACKING	:	1 ltr, 4 ltr and 18 ltr

### Technical Data

BASE RESIN	:	Highly aliphatic hydrocarbons.
COLOR	:	Colourless
DENSITY	:	Approx. 0.9 kg/ltr
FLASH POINT	:	>40°C

### Safety Precaution

DANGEROUS GOODS CLASSIFICATION	Flammable liquids Class 3	
SHELF-LIFE	:	24 months.
APPLICATION CONDITIONS	:	Keep product away from sources of heat, naked flames and sparks. Avoid contamination of the skin, eyes and clothing. Avoid breathing the vapour and avoid accidental ignition of the liquid. Wear protective equipment as and when appropriate.
HEALTH & SAFETY PRECAUTIONS	:	Ingestion : Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting. Skin contact : Flush immediately with water and remove contaminated clothing. Use soap if available. If irritation persists refer for medical attention. Eye contact : Flush immediately with water and get medical care. Inhalation : Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.

Notes: Product data is based on in-house testing methods modified from BS3900/ASTM.

Content will be updated without prior notice.

Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.

Technical Bulletin No.CX316/201020