



# CAMEL

## 252 Excellent Interior Emulsion Anti-Mould & Virus

### PRODUCT INTRODUCTION

<b>Recommended Uses</b>	Suitable for interior ceilings and plastered cementitious walls.
<b>Description</b>	This product is specially formulated with anti-viral and anti-bacterial performance. This product is anti-bacterial and mould proof, and it's proven to be effective against virus H1N1 and Staphylococcus aureus, efficacy is over 99.9%.
<b>Features</b>	<ul style="list-style-type: none"> <li>✓ 380 upgraded formula</li> <li>✓ Certified under the HKGBC Green Product Accreditation and Standards (HK G-Pass) and this product is rated PLATINUM - CICGPC-L-21146(RMC)</li> <li>✓ Anti-viral (ISO 21702:2019)</li> <li>✓ Anti-bacterial</li> <li>✓ 5 years mould proof warranty</li> <li>✓ Low odour and environmental friendly</li> <li>✓ Good hiding</li> </ul>
<b>5 Years Mould Warranty</b>	<ul style="list-style-type: none"> <li>• Warranty registration: <a href="http://www.camel.com.hk/zh-hant/warranty/">www.camel.com.hk/zh-hant/warranty/</a></li> <li>• By register the online warranty service, you'll be able to enjoy 5 year of Mould Free Warranty for this product.</li> <li>• The warranty is valid only in Hong Kong and Macau area.</li> <li>• Please read the service policy before register.</li> <li>• Yip's Camel (HK) Ltd. reserves the right to change or cancel service for any incorrect information.</li> </ul>
<b>Standard Packing</b>	1L, 5L

### TECHNICAL DATA

<b>Base Resin</b>	Acrylic copolymer
<b>Color</b>	Standard colors or personalized color by computerized tinting machine
<b>Finish</b>	Matt
<b>Calculated Coverage</b>	Around 12m <sup>2</sup> /ltr. @30 microns dry film thickness per coat (Actual coverage depends on surface conditions and also application conditions.)
<b>Drying Time (@ 25°C)</b>	<ul style="list-style-type: none"> <li>• Touch Dry --- 1 hour</li> <li>• Hard Dry --- 2 hours</li> <li>• Overcoating --- Minimum 2 hours</li> </ul>

#### Remarks:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.



# CAMEL

## 252 Excellent Interior Emulsion Anti-Mould & Virus

### APPLICATION

<b>Recommended Primer</b>	Camel Alkali Resistant Wall Sealer MA473 or Camel Professional Water Sealer S200
<b>Recommended Thinner</b>	Clear Water
<b>Method of Application</b>	<ul style="list-style-type: none"> <li>Ready-to-use after thinning with clear water and stirring thoroughly</li> <li>Thinning Ratio: Brush / Roller - Dilute 10 parts of the paint with around 1 to 4 parts of clear water (10 : ~ 1 to 4 by volume).</li> </ul>
<b>Surface Preparation</b>	<p>For new wall</p> <ul style="list-style-type: none"> <li>The substrate should be cured at least 30 days. The alkalinity (pH) of the surface should be &lt; 10 before painting and water content of the substrate should be &lt; 15%.</li> <li>Fill up cracks and depression to get a smooth surface with appropriate filler.</li> <li>Ensure the surfaces to be coated are sound, clean, free from dust, rust, oil, grease, moisture and foreign matters.</li> </ul> <p>For recoated surface</p> <ul style="list-style-type: none"> <li>All chalked and scaled materials must be removed before painting.</li> <li>Apply patching paste to get a smooth surface before painting.</li> <li>Apply AquaPro Super Anti-Mould Wash 111 (dilute 2 parts of Super Anti-Mould Wash 111 with 1 part of clear water) on mould affected area, and stay more than 6 hours.</li> <li>After 6 hours, clean with new towel and water.</li> <li>Use new towels in each process, to avoid cross contamination.</li> <li>Ensure the surfaces to be coated are sound, clean, free from dust, rust, oil, grease, moisture and foreign matters.</li> </ul>

#### Remarks:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.



# CAMEL

## 252 Excellent Interior Emulsion Anti-Mould & Virus

### STORAGE

<b>Dangerous Goods Classification</b>	Not applicable
<b>Shelf-Life</b>	36 Months
<b>Application Conditions</b>	<ul style="list-style-type: none"> <li>Maintain temperature in areas to receive coatings at minimum 8°C, during application and until coatings have cured.</li> <li>Avoid applying the product when relative humidity above 85%.</li> <li>Adequately ventilate areas where coatings are being applied. Maintain a reasonably dust-free atmosphere for duration of work.</li> <li>Protect adjacent surfaces not scheduled to receive coatings from damage and overcoat.</li> <li>Post "Wet Coating" signs while work is in progress and while coatings are curing.</li> </ul>
<b>Product Storage, Delivery &amp; Handling</b>	<ul style="list-style-type: none"> <li>Material to be delivered and stored in undamaged, original manufacturers' containers.</li> <li>Keep container closed when not in use.</li> <li>Store at cool, dry place. Store above freezing point.</li> </ul>
<b>Health &amp; Safety Precautions</b>	<ul style="list-style-type: none"> <li>Ingestion: Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting.</li> <li>Eye contact: Flush immediately with water and get medical care.</li> <li>Skin contact: Flush immediately with water and remove contaminated clothing. If irritation persists, refer for medical attention.</li> <li>Inhalation: Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.</li> </ul>
<b>Type of Regulated Paint</b>	Flat Coatings P09-02 (under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong)
<b>VOC content</b>	Not exceeding 50gm/litre ( <b>Ready to use</b> )

#### Remarks:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.