

CAMEL

EXTERIOR / INTERIOR WALL FINISH (MATT)

MA200

Product Introduction

RECOMMENDED USES	:	Suitable for interior and exterior surfaces of masonry, concrete and plaster.
DESCRIPTION	:	This modified acrylic emulsion paint is formulated for interior and exterior application. <ul style="list-style-type: none"> ● Outstanding Opacity ● Fungus Resistant ● Good Exterior Durability ● Ease Of Application ● Cost effective ● Good alkaline resistance ● Good levelling properties ● Flat finish, blurs imperfections of the walls
STANDARD PACKING	:	16kg

Technical Data

BASE RESIN	:	Modified acrylic Emulsion
COLOR	:	White
FINENESS	:	Maximum 50 microns
FINISH	:	Matt
CALCULATED COVERAGE	:	Approx. 7 - 8 sq. m/ ltr. at 30 microns dry film thickness, actual coverage depends on application conditions, surface conditions and also wastage.
DRYING TIME	:	
Touch Dry	:	1 hour
Recoatable Dry	:	2 hours

Application

RECOMMENDED PRIMER	:	Camel Alkali Resistant Wall Sealer MA473 or Camel Professional Water Sealer S200
RECOMMENDED UNDERCOAT	:	Not applicable
RECOMMENDED THINNER	:	Water
METHOD OF APPLICATION	:	
Recommended coats	:	2 coats
For Brush	:	Dilute 10 parts of paint with no more than 2 parts of water.
For Roller	:	Dilute 10 parts of paint with no more than 2 parts of water.
	:	Painting is recommended to be carried out on fine day.
	:	Surfaces to be coated must be sound, clean, non-dusting, free from oil, grease, moisture and foreign particles. For recoating old surfaces, all chalked and scaled materials must be removed before painting.
	:	Stir the paint well before use.

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.

CAMEL

EXTERIOR / INTERIOR WALL FINISH (MATT)

MA200

Safety Precaution

DANGEROUS GOODS CLASSIFICATION	:	Non-dangerous goods
SHELF-LIFE	:	24 months.
APPLICATION CONDITIONS	:	<p>Maintain temperature in areas to receive coatings at minimum 5 °C, during application and until coatings have cured.</p> <p>Moisture content of substrate should less than 10%, pH should less than 10.</p> <p>Do not apply paint on wet, cold days (temperature below 5 °C, relative humidity greater than 85%) or windy days.</p> <p>Adequately ventilate areas where coatings are being applied. Maintain a reasonably dust-free atmosphere for duration of work.</p> <p>Protect adjacent surfaces not scheduled to receive coatings from damage and overcoat.</p> <p>Post "Wet Coating" signs while work is in progress and while coatings are curing.</p>
PRODUCT STORAGE & HANDLING	:	<p>Weight : Approx. 16 kg</p> <p>Delivery & Handling : Material to be delivered and stored in undamaged, original manufacturers' containers.</p> <p>: Keep container closed when not in use.</p> <p>: Store at cool, dry place.</p>
HEALTH & SAFETY PRECAUTIONS	:	<p>Ingestion : Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting.</p> <p>Skin contact : Flush immediately with water and remove contaminated clothing. Use soap if available. If irritation persists refer for medical attention.</p> <p>Eye contact : Flush immediately with water and get medical care.</p> <p>Inhalation : Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.</p>
REGULATED PRODUCT CODE	:	Flat Coatings P09-02
VOC CONTENT	:	≤ 50g/ltr

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.