

**CAMEL****P288 All-in-One Water-Borne Based Varnish****PRODUCT INTRODUCTION**

Recommended Uses	Suitable for interior & exterior surfaces of concrete, cement, plaster and masonry.
Description	This water-borne based varnish is formulated specially for priming interior & exterior wall surfaces. It forms a tough film of excellent adhesion, binding and also resistance to alkali & water. This product can be also directly mixed with vegetable glue and whitening powder to improve the strength of plaster.
Features	<ul style="list-style-type: none">✓ Excellent binding strength for powdery plaster✓ Well balance of penetration power and film forming✓ Excellent Adhesion to substrate✓ Excellent Water and Alkali Resistance✓ Low VOC & no odour✓ Compatible with vegetable glue and whitening powder✓ Can be used as a base for wallpaper
Standard Packing	1L, 4L

TECHNICAL DATA

Base Resin	Modified acrylic copolymer
Color	Clear
Finish	Semi-gloss
Calculated Coverage	Around 12m ² /ltr. @20 microns dry film thickness per coat (Actual coverage depends on surface conditions and also application conditions.)
Drying Time (@ 25°C)	<ul style="list-style-type: none">• Touch Dry --- 1 hour• Hard Dry --- 2 hours• Overcoating --- Minimum 4 hours

Remarks:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.



CAMEL

P288 All-in-One Water-Borne Based Varnish

APPLICATION

Recommended Thinner	Clear Water
Cleaning Solvent	Clear Water
Method of Application	<p>SHAKE WELL BEFORE USE</p> <p>As wall sealer</p> <ul style="list-style-type: none"> Brush / Roller - Ready-to-use, thinned if necessary. Dilute 10 parts of paint with 0-1 parts of water by volume. <p>As plaster enhancer</p> <ul style="list-style-type: none"> Add appropriate amount P288 directly in vegetable glue and whitening powder, mix well until homogeneous plaster is formed. <p>Recommended Application</p> <ul style="list-style-type: none"> Painting is recommended to carry out on fine day. Surfaces to be coated must be sound, clean, free from dust, rust, oil, grease, moisture and foreign matters. For recoating old surfaces, all chalked and scaled materials must be removed before painting. Fresh concrete must be allowed to cure sufficiently (i.e. approximately 28 days) prior to application.

Remarks:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.

**CAMEL****S200A Superior Penetrating Water Sealer****STORAGE**

Dangerous Goods Classification	Not applicable
Shelf-Life	24 Months
Application Conditions	<ul style="list-style-type: none"> Maintain temperature in areas to receive coatings at minimum 7°C, during application and until coatings have cured. Avoid applying the product when relative humidity above 85%. Adequately ventilate areas where coatings are being applied. Maintain a reasonably dust-free atmosphere for duration of work. Protect adjacent surfaces not scheduled to receive coatings from damage and overcoat. Post “Wet Coating” signs while work is in progress and while coatings are curing.
Product Storage, Delivery & Handling	<ul style="list-style-type: none"> Material to be delivered and stored in undamaged, original manufacturers’ containers. Keep container closed when not in use. Store at cool, dry place. Store above freezing point.
Health & Safety Precautions	<ul style="list-style-type: none"> Ingestion: Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting. Eye contact: Flush immediately with water and get medical care. Skin contact: Flush immediately with water and remove contaminated clothing. If irritation persists, refer for medical attention. Inhalation: Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.
Type of Regulated Paint	Primers, Sealers and Undercoaters P10-11 (under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong)
VOC content	Not exceeding 200gm/litre (Ready to use)

Remarks:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.