



CAMEL

AX473 Interior & Exterior Wall Sealer

PRODUCT INTRODUCTION

Recommended Uses	Suitable for interior & exterior surfaces of concrete, cement, plaster and masonry.
Description	This sealer is formulated specially for priming well-prepared interior & exterior plastered wall surfaces. It forms a tough film of excellent adhesion, hiding, binding and also resistance to alkali & water.
Features	✓ Excellent Adhesion to Substrate ✓ Excellent Hiding ✓ Excellent Binding Strength ✓ Excellent Water and Alkali Resistance ✓ Low VOC & No Odour ✓ Ease of Application
Standard Packing	18L

TECHNICAL DATA

Base Resin	Modified acrylic copolymer
Color	White
Finish	Matt
Calculated Coverage	Approx. 16m ² / ltr. at 25 microns dry film thickness depends on surface condition and application method. (Actual coverage depends on surface conditions and also application conditions.)
Recommended Film Thickness	• Wet: 60-80 microns • Dry : 19-25 microns
Drying Time	• Touch Dry: 1 hour • Hard Day: 2 hours • Overcoating --- Minimum 4 hours

APPLICATION

Recommended Thinner	Water
Cleaning Solvent	Water
Method of Application	• Thinning Ratio: Brush / Roller – Ready for use, thinned if necessary. Dilute 10 parts of paint with 0-1 parts of water by volume. • Recommended no. of coats: 1 coat • Recommended Application Painting is recommended to carry out on fine day. Surfaces to be coated must be sound, clean, free from dust, rust, oil, grease, moisture and foreign matters. For recoating old surfaces, all chalked and scaled materials must be removed before painting. Fresh concrete must be allowed to cure sufficiently (i.e. approximately 28 days) prior to application.

Remarks:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.

**CAMEL****AX473 Interior & Exterior Wall Sealer****STORAGE**

Dangerous Goods Classification	Non-dangerous goods
Shelf-Life	24 Months
Application Conditions	- Maintain temperature in areas to receive coatings at minimum 7 deg. C, during application and until coatings have cured. - Adequate ventilated areas where coating is being applied. Maintain a reasonably dust-free atmosphere for duration of works. - Protect adjacent surfaces not scheduled to receive coating from damage and overcoat. - Post 'Wet Coating' signs while work is in progress and while coating are curing.
Product Storage, Delivery & Handling	- Material to be delivered and stored in undamaged, original manufacturers' containers. - Keep container closed when not in use. - Stir the paint well before use. - Store at cool, dry place. Store above freezing point.
Health & Safety Precautions	- Ingestion: Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting. - Skin contact: Flush immediately with water and remove contaminated clothing. Use soap if available. If irritation persists, refer for medical attention. - Eye contact: Flush immediately with water and get medical care. - Inhalation : Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur
Type of Regulated Paint	Primers, Sealers and Undercoaters P10-11 (under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong)
VOC content	Not exceeding 200gm/litre (Ready to use)

Remarks:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.