

**Camel**  
**Professional Exterior / Interior Wall Finish**  
**3 Years Warranty (Matt)**  
**MA476 series**

**PRODUCT INTRODUCTION**

Recommended Uses	Suitable for interior and exterior surfaces of masonry, concrete and plaster.
Description	MA476 series is a premium quality matt emulsion paint specially designed for protection and decoration of exterior and interior wall surfaces.
Features	<ul style="list-style-type: none"> <li>● 3 Years Color Warranty</li> <li>● For Exterior / Interior Wall</li> <li>● Save Time</li> </ul>
Standard Packing	5L & 16kg

**TECHNICAL DATA**

Base Resin	Acrylic
Color	As per color card with standard colors ; or tailor-made colors on request
Standard Accelerated Weathering	No chalking, cracking & serious color fading observed after 750 hours in UV / Condensation Screening Device.
Finish	Matt
Calculated Coverage	Around 13m <sup>2</sup> /ltr. @30 microns dry film thickness per coat Actual coverage depends on surface conditions and also application conditions.
Drying Time	<ul style="list-style-type: none"> <li>● Touch Dry --- 1 hour</li> <li>● Hard Dry --- 2 hours</li> </ul>

**APPLICATION**

Recommended Thinner	Clear Water
Recommended Primer	Camel Alkali Resistant Wall Sealer MA473 or Camel Professional Water Sealer S200
Recommended Undercoats	Camel Textured Base Coat MA471
Method of Application	<ul style="list-style-type: none"> <li>● Ready-to-use after thinning with clear water and stirring thoroughly.</li> <li>● Thinning Ratio Brush / Roller / Spray --- Dilute 10 parts of the paint with around 2 parts of clear water (10 : 2 by volume).</li> <li>● Recommended no. of coats : 2 coats</li> </ul>

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.

**Camel**  
**Professional Exterior / Interior Wall Finish**  
**3 Years Warranty (Matt)**  
**MA476 series**

**APPLICATION**

Recommendations for Application	<ul style="list-style-type: none"> <li>● Painting is recommended to carry out on fine day.</li> <li>● Surfaces to be coated must be sound, clean, free from dust, rust, oil, grease, moisture and foreign matters. For recoating old surfaces, all chalked and scaled materials must be removed before painting.</li> </ul>
---------------------------------	---

**SAFETY PRECAUTION**

Dangerous Goods Classification	Not applicable
Shelf-Life	36 months
Application Conditions	<ul style="list-style-type: none"> <li>● Maintain temperature in areas to receive coatings at minimum 7 deg. C, during application and until coatings have cured.</li> <li>● Adequately ventilate areas where coatings are being applied. Maintain a reasonably dust-free atmosphere for duration of work.</li> <li>● Protect adjacent surfaces not scheduled to receive coatings from damage and overcoat.</li> <li>● Post "Wet Coating" signs while work is in progress and while coatings are curing.</li> </ul>
Product Storage, Delivery & Handling	<ul style="list-style-type: none"> <li>● Material to be delivered and stored in undamaged, original manufacturers' containers.</li> <li>● Keep container closed when not in use.</li> <li>● Store at cool, dry place.</li> </ul>
Health & Safety Precautions	<ul style="list-style-type: none"> <li>● Ingestion --- Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting.</li> <li>● Eye contact --- Flush immediately with water and get medical care.</li> <li>● Skin contact --- Flush immediately with water and remove contaminated clothing. If irritation persists, refer for medical attention.</li> <li>● Inhalation --- Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.</li> </ul>
Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong	Flat Coatings P09-02
VOC content (ready to use)	Not exceeding 50gm/litre

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.