

Camel

Weatherproof Exterior Wall Finish

MA488 series

PRODUCT INTRODUCTION

Recommended Uses	Suitable for exterior surfaces of masonry, concrete and plaster.
Description	MA488 series is a premium quality emulsion paint specially designed for protection and decoration of exterior wall surface.
Features	● High opacity ● Excellent weather proof ● Excellent resistance to fungus and algae ● Ease of wash and maintenance ● Ease of application ● Compatible for Texture Coating
Standard Packing	4L & 18L

TECHNICAL DATA

Base Resin	Acrylic Emulsion
Color	As per color card with standard colors ; or tailor-made colors on request
Standard Accelerated Weathering	No chalking, cracking & very slight color fading observed after 1500 hours in UV / Condensation Screening Device. (1000 Hours are equivalent to approx. 5 years)
Finish	Eggshell
Calculated Coverage	Around 13.3m ² /ltr. @30 microns dry film thickness per coat Actual coverage depends on surface conditions and also application conditions.
Drying Time	● Touch Dry --- 1 hour ● Hard Dry --- 2 hours

APPLICATION

Recommended Thinner	Clear Water
Recommended Primer	Camel Alkali Resistant Wall Sealer MA473 or Camel Professional Water Sealer S200
Recommended Undercoats	Camel Textured Base Coat MA471
Method of Application	● Ready-to-use after thinning with clear water and stirring thoroughly. ● Thinning Ratio Brush / Roller / Spray --- Dilute 10 parts of the paint with around 1 - 3 parts of clear water (10 : 1 - 3 by volume). ● Recommended no. of coats : 2 coats

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.

Camel

Weatherproof Exterior Wall Finish

MA488 series

APPLICATION	
Recommendations for Application	● Painting is recommended to carry out on fine day. ● Surfaces to be coated must be sound, clean, free from dust, rust, oil, grease, moisture and foreign matters. For recoating old surfaces, all chalked and scaled materials must be removed before painting.
SAFETY PRECAUTION	
Dangerous Goods Classification	Not applicable
Shelf-Life	36 months
Application Conditions	● Maintain temperature in areas to receive coatings at minimum 7 deg. C, during application and until coatings have cured. ● Adequately ventilate areas where coatings are being applied. Maintain a reasonably dust-free atmosphere for duration of work. ● Protect adjacent surfaces not scheduled to receive coatings from damage and overcoat. ● Post “Wet Coating” signs while work is in progress and while coatings are curing.
Product Storage, Delivery & Handling	● Material to be delivered and stored in undamaged, original manufacturers’ containers. ● Keep container closed when not in use. ● Store at cool, dry place.
Health & Safety Precautions	● Ingestion --- Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting. ● Eye contact --- Flush immediately with water and get medical care. ● Skin contact --- Flush immediately with water and remove contaminated clothing. If irritation persists, refer for medical attention. ● Inhalation --- Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.
Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong	Non-flat Coatings P09-06
VOC content (ready to use)	Not exceeding 150gm/litre

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.