

VIVA
TEXTURED LATEX PAINT
K100 – LINE

Product Introduction

RECOMMENDED USES	:	Suitable for interior and exterior surfaces of masonry, concrete and plaster.
DESCRIPTION	:	A durable, easy to apply textured vinyl versatate copolymer emulsion paint formulated for interior and exterior application. <ul style="list-style-type: none"> ● Excellent exterior durability. ● Excellent resistance to fungus and algae. ● Excellent colour retention. ● Excellent resistance to alkalis. ● High opacity. ● Ease of application. ● Economical Emulsion Paint. ● Compatible for Texture Coating. ● No added Lead & Mercury.
STANDARD PACKING	:	4 litre & 18 litre

Technical Data

BASE RESIN	:	Vinyl Versatate Copolymer Emulsion.
COLOR	:	As per color card , Tailor-made colors on requests
FINISH	:	Matt
CALCULATED COVERAGE	:	Approx. 13.3 sq.m / ltr. at 30 Microns dry film thickness.
DRYING TIME	:	
Touch Dry	:	1 hour
Hard Dry	:	2 hours
Over coating@20°C	:	
Minimum	:	3 hours
Maximum	:	- Indef.

Application

RECOMMENDED PRIMER	:	Camel Brand Alkali Resistant Wall Sealer MA473 or Camel Professional Water Sealer S200
RECOMMENDED THINNER	:	Water (Maximum 30 % Addition)
CLEANING SOLVENT	:	Water
METHOD OF APPLICATION	:	
For Brush	:	Dilute 10 parts of paint with 3 parts of water by volume.
For Roller	:	Dilute 10 parts of paint with 2 parts of water by volume

Notes: Product data is based on in-house testing methods modified from BS3900/ASTM.
Content will be updated without prior notice.
Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.

VIVA
TEXTURED LATEX PAINT
K100 – LINE

Safety Precaution

DANGEROUS GOODS CLASSIFICATION	:	Not applicable.
SHELF-LIFE	:	24 months.
APPLICATION CONDITIONS	:	Maintain temperature in areas to receive coatings at minimum 7 deg. C, during application and until coatings have cured. Adequately ventilate areas where coating are being applied. Maintain a reasonably dust-free atmosphere for duration of works Protect adjacent surfaces not scheduled to receive coating from damage and overcoat. Post 'Wet Coating' signs while work is in progress and while coating are curing.
OTHER CONSIDERATIONS	:	Material to be delivered and stored in undamaged, original manufacturers' containers. Keep container closed when not in use. Stir the paint well before use. Store at cool, dry place.
HEALTH & SAFETY PRECAUTIONS	:	Ingestion : Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting. Skin contact : Flush immediately with water and remove contaminated clothing. Use soap if available. If irritation persists refer for medical attention. Eye contact : Flush immediately with water and get medical care. Inhalation : Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.
REGULATED PRODUCT CODE	:	Flat Coatings P09-02
VOC CONTENT	:	≤ 50g/ltr

Notes: Product data is based on in-house testing methods modified from BS3900/ASTM.
 Content will be updated without prior notice.
 Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.

Technical Bulletin No.K100/230310