

# Camel Professional Brushing Lacquer CB series

## PRODUCT INTRODUCTION

Recommended Uses	For the decoration and re-decoration of architectural wooden and metallic surfaces.
Description	A brushing lacquer with a good balance of drying speed, brushability and levelling. The tough, flexible film has excellent decorative quality and durability. The lacquer may also be applied by spraying.
Features	<ul style="list-style-type: none"> <li>● Fast air dry</li> <li>● Excellent flow properties</li> <li>● Excellent brush ability</li> <li>● Anti-corrosive from alcohol and detergent</li> <li>● High film build</li> <li>● High opacity</li> <li>● Excellent gloss</li> <li>● Could obtain lower gloss level by using Camel Matting Agent MA467</li> </ul>
Standard Packing	430 ml, 1L & 4L

## TECHNICAL DATA

Base Resin	Nitrocellulose
Color	As per color card with standard colors; or tailor-made colors on request.
Finish	High Gloss
Calculated Coverage	Around 13m <sup>2</sup> /ltr. @25 microns dry film thickness per coat Actual coverage depends on surface conditions and also application conditions.
Drying Time	<ul style="list-style-type: none"> <li>● Touch Dry --- 10 minutes</li> <li>● Hard Dry --- 3 hours</li> <li>● Overcoating --- minimum 20 minutes, maximum indefinite.</li> </ul>

## APPLICATION

Recommended Sealer	Wood--- AquaPro Enamel Primer 113 Metal--- AquaPro Rust-Proof Metal Primer 103
Recommended Thinner	Camel Low VOC Lacquer Thinner 139
Method of Application	<ul style="list-style-type: none"> <li>● Thinning Ratio --- Dilute 1 part of paint with 3 parts of thinner by volume.</li> </ul>
Recommendations for Application	<ul style="list-style-type: none"> <li>● Painting is recommended to carry out on fine day.</li> <li>● Surfaces to be coated must be sound, clean, free from dust, rust, oil, grease, moisture and foreign matters. For recoating old surfaces, all chalked and scaled materials must be removed before painting.</li> <li>● Stir the paint well before use.</li> </ul>

### Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.

**Camel**  
**Professional Brushing Lacquer**  
**CB series**

**SAFETY PRECAUTION**

Dangerous Goods Classification	Class 3
Shelf-Life	24 months
Application Conditions	<ul style="list-style-type: none"> <li>● Adequately ventilate areas where coatings are being applied. Maintain a reasonably dust-free atmosphere for duration of work.</li> <li>● Protect adjacent surfaces not scheduled to receive coatings from damage and overcoat.</li> <li>● Post “Wet Coating” signs while work is in progress and while coatings are curing.</li> </ul>
Product Storage & Handling	<ul style="list-style-type: none"> <li>● Delivery &amp; Handling</li> </ul> <p>---Material to be delivered and stored in undamaged, original manufacturers’ containers.</p> <p>---Keep container closed when not in use.</p> <p>---Stir the paint well before use.</p> <p>---Store at cool, dry place.</p>
Health & Safety Precautions	<ul style="list-style-type: none"> <li>● Ingestion --- Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting.</li> <li>● Eye contact --- Flush immediately with water and get medical care.</li> <li>● Skin contact --- Flush immediately with water and remove contaminated clothing. If irritation persists, refer for medical attention.</li> <li>● Inhalation --- Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.</li> </ul>
Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong	Pigmented lacquers P08-14
VOC content (ready to use)	Not exceeding 250gm/litre

Notes:

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.