



## AQUAPRO BRUSHING LACQUER 127 SERIES

“AquaPro Brushing Lacquer 127 series” is a high quality, multi-purpose coating for a variety of interior applications on all metal and wood surfaces. This paint features jet dry, good leveling during application, with low VOC content and excellent durability.

Usage	Suitable for all metal and wood surfaces.		
Finish	High Gloss, Semi Gloss, Low Gloss, Matt		
Color	Standard Colors, 1,050+ computerized tinting colors & tailor-made colors on request		
Packing	1 Liter, 3 Liters		
Advantages	<ul style="list-style-type: none"> <li>✓ Jet dry</li> <li>✓ High gloss</li> <li>✓ Good gloss retention</li> <li>✓ Low VOC</li> <li>✓ Ease of application</li> </ul>		
Base Resin	Synthetic Latex		
Drying Time			
– Touch Dry	1 hour		
– Hard Dry	2 hours		
– Overcoating	Minimum 4 hours		
Coverage	Around 19.2m <sup>2</sup> /ltr. @25 microns dry film thickness per coat Actual coverage depends on surface conditions and also application conditions.		
Shelf Life	36 months		
Recommended Primer	<b>AquaPro Matting Agent 110</b> This matting agent is specially formulated for lowering the gloss level of water based paint. Desired gloss level of paint such as Semi Gloss and Matt can be easily achieved. It is suitable for all AquaPro product series.		
Recommended Coating System	Galvanized steel (G.I.)	Primer	Water-borne GI Primer AR033
		Topcoat	AquaPro Brushing Lacquer 127
	Metal	Primer	AquaPro Rust-Proof Metal Primer 103
		Undercoat	AquaPro Brushing Enamel Primer 113
		Topcoat	AquaPro Brushing Lacquer 127
	Wood	Undercoat	AquaPro Brushing Enamel Primer 113
		Topcoat	AquaPro Brushing Lacquer 127
Application Method	Ready-to-use after thinning with clear water and stirring thoroughly		
Recommended No. of coat	2 coats		
Thinning Ratio			
– Brush/Roller	Dilute 10 parts of the paint with around 1 to 2 parts of clear water (10-20%)		

Technical Bulletin No.: 127/250430

葉氏駱駝(香港)有限公司 YIP'S CAMEL (HONG KONG) LIMITED

香港灣仔告士打道77-79號富通大廈27樓

27/F., Fortis Tower, 77-79 Gloucester Road, Wanchai, Hong Kong

電話 Tel: (852) 2675 2333

傳真 Fax: (852) 2675 2332

電郵 Email: info@camel.com.hk

網址 Website: <http://www.camel.com.hk>



<b>Application</b>	<ol style="list-style-type: none"> <li>1. Painting is recommended to carry out on fine day.</li> <li>2. Surfaces to be coated must be sound, clean, free from dust, rust, oil, grease, moisture and foreign matters. For recoating old surfaces, all chalked and scaled materials must be removed before painting.</li> <li>3. Stir the paint well before use.</li> <li>4. The product would be cured to maximum physical properties in 7-8 days.</li> </ol>
<b>Conditions</b>	<ul style="list-style-type: none"> <li>- Maintain temperature in areas to receive coatings at minimum 5°C during application and until coatings have cured.</li> <li>- Avoid applying the product when relative humidity above 85%.</li> <li>- Adequately ventilate areas where coatings are being applied. Maintain a reasonably dust-free atmosphere for duration of work.</li> <li>- Protect adjacent surfaces not scheduled to receive coatings from damage and overcoat.</li> <li>- Post "Wet Coating" signs while work is in progress and while coatings are curing.</li> <li>- Material to be delivered and stored in undamaged, original manufacturers' containers.</li> <li>- Keep container closed when not in use</li> <li>- Store at cool, dry place. Store above freezing point.</li> </ul>
<b>Health &amp; Safety Precautions</b>	
<ul style="list-style-type: none"> <li>- <i>Ingestion</i></li> <li>- <i>Eye contact</i></li> <li>- <i>Skin contact</i></li> <li>- <i>Inhalation</i></li> </ul>	<p>Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting.</p> <p>Flush immediately with water and get medical care.</p> <p>Flush immediately with water and remove contaminated clothing. If irritation persists, refer for medical attention.</p> <p>Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.</p>

**Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong:** Clear: Clear wood finishes (lacquers) P10-01; General colour: Pigmented lacquers P08-14

**VOC content (ready to use):** Clear: Not exceeding 400gm/Liter; General colour: Not exceeding 275gm/Liter

## NOTES

- Product data is based on in-house testing methods modified from BS3900/ASTM.
- Content will be updated without prior notice.
- Surface preparation, application method and condition, etc. may affect product performance. We are not responsible for the performance, unless agreed in writing by us.

Technical Bulletin No.: 127/250430