

CAMEL

WATER-BORNE GI PRIMER

AR033

Product Introduction

RECOMMENDED USES	For priming galvanized steel, iron, aluminum and copper.
DESCRIPTION	<p>This product is a water based anti-corrosive primer suitable for various metal substrates</p> <ul style="list-style-type: none"> ● Environmentally friendly ● Non-toxic ● Ready for use ● Overcoatable by alkyd & emulsion topcoat ● Zinc Phosphate content 10 percentage by weight of total pigment
STANDARD PACKING	4L & 18L

Technical Data

BASE RESIN	Modified acrylic copolymer
COLOR	White
GLOSS	Flat
CALCULATED COVERAGE	Approx. 12.8 sq. m/ ltr. at 25 microns dry film thickness depends on surface condition and application method.
DRYING TIME Touch dry Hard dry Over coating@20°C Minimum Maximum	30 minutes 1 hours 4 hours -Indef.

Application

RECOMMENDED THINNER	Water
CLEANING SOLVENT	Water

Notes: Product data is based on in-house testing methods modified from BS3900/ASTM.
 Content will be updated without prior notice.
 Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.

CAMEL

WATER-BORNE GI PRIMER

AR033

Application

METHOD OF APPLICATION By Brush/Roller By Spray	Ready for use, thinned if necessary. Dilute 10 parts of paint with 1 part of water by volume. Painting is recommended to carry out on fine day. Surfaces to be coated must be sound, clean, non-dusting, free from oil, grease, moisture and foreign particles. For recoating old surfaces, all chalked and scaled materials must be removed before painting. Stir the paint well before use.
---	---

Safety Precaution

DANGEROUS GOODS CLASSIFICATION	Non-dangerous goods
SHELF-LIFE	18 Months
APPLICATION CONDITIONS	Maintain temperature in areas to receive coatings at minimum 7 deg. C, during application and until coatings have cured. Adequate ventilated areas where coating is being applied. Maintain a reasonably dust-free atmosphere for duration of works. Protect adjacent surfaces not scheduled to receive coating from damage and overcoat. Post 'Wet Coating' signs while work is in progress and while coating are curing.
HEALTH & SAFETY PRECAUTIONS	Ingestion : Send the affected person to hospital or obtain medical attention immediately. Do not induce vomiting. Skin contact : Flush immediately with water and remove contaminated clothing. Use soap if available. If irritation persists refer for medical attention. Eye contact : Flush immediately with water and get medical care. Inhalation : Remove the affected person to fresh air and obtain medical attention if rapid recovery does not occur.
Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong	Primers, Sealers, Undercoats P10-11
VOC CONTENT (ready to use)	Not exceeding 200gm/litre

Notes: Product data is based on in-house testing methods modified from BS3900/ASTM.
Content will be updated without prior notice.
Surface preparation, application method and condition will affect product performance. We are not responsible for the performance, unless agreed in writing by us.